



MATERIAL SAFETY DATA SHEET

Schnee-Morehead®, Inc.

CAULK

pg 1 of 6

1/8/2009

SECTION I - IDENTIFICATION

PRODUCT NAME : SM5522 Clear

PRODUCT CODE : SM5522C

DESCRIPTION : Acrylic Bedding Sealant

HAZARDOUS CLASSIFICATION: Non Regulated

PROPER SHIPPING NAME : Not Applicable

SHIPPING DESCRIPTION : Not Required

H.M.I.S RATINGS: H F R P
1 1 0 G

SECTION II - MANUFACTURER

MANUFACTURER'S NAME : Schnee-Morehead, Inc.

STREET ADDRESS : 111 North Nursery Road, Irving, Texas

INFORMATION PHONE : 972-438-9111

EMERGENCY PHONE : 800-424-9300

DATE PREPARED : March 6, 2007

SUPERSEDES DATE : March 3, 2004

SECTION III - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	ACGIH TLV	OTHER LIMITS	PERCENT (WGT)
Toluene	108-88-3	200 ppm TWA	50 ppm TWA	188 mg/m3 TWA	27-31

SECTION IV - PHYSICAL PROPERTIES

SPECIFIC GRAVITY (H₂O=1) : 1.06

BOILING POINT : 110.6°C (Toluene)

NONVOLATILE (% WEIGHT) : 69% Min

MELT/FREEZE PT : N/A

SOLUBILITY IN WATER : Insoluble

VAPOR DENSITY : 3.2 (Toluene)

EVAPORATION RATE (BuAc=1) : 1.9 (Toluene)

VAPOR PRESSURE : 28.5 mm (Toluene)

VOLATILE ORGANIC CONTENT : 2.73 lbs/gal, 327 g/l

APPEARANCE/ODOR

: Clear, pumpable material - aromatic odor

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : 49.0°F

METHOD USED : Tag Closed Cup (ASTM D56)

FLAMMABLE LIMITS IN AIR BY VOLUME

LOWER : 1.27 (Toluene)

UPPER : 7.1 (Toluene)

EXTINGUISHING MEDIA : Use carbon dioxide, dry chemical, foam or water spray.

SPECIAL FIREFIGHTING PROCEDURES : Firefighters should wear a self contained breathing apparatus and full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARD : This product, in an uncured state, emits vapors that are volatile and flammable. Once this product has cured, it is nonflammable.

SECTION VI - REACTIVITY DATA

STABILITY : Stable

CONDITIONS TO AVOID : Avoid heat, sparks and any other sources of ignition.


INCOMPATIBILITY (MATERIALS TO AVOID) : Avoid contact with oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS : During a fire this material may form carbon dioxide, carbon monoxide and other various hydrocarbon fumes.

HAZARDOUS POLYMERIZATION : Will not occur.

SM5522CMSDS.doc

Page 1 of 3



Caulk
pg 2 of 6

MATERIAL SAFETY DATA SHEET

Schnee-Morehead®, Inc.

SECTION VII - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY : **INHALATION?** : Yes **SKIN?** : Yes **INGESTION?** : Not likely
HEALTH HAZARDS (ACUTE AND CHRONIC) : Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and possible headaches. Excessive skin contact can cause irritation, drying and possible edema.

CARCINOGENICITY: **NTP?** : No **IARC MONOGRAPHS?** : No **OSHA REGULATED?** : Yes

SIGNS AND SYMPTOMS OF EXPOSURE: Chronic effects of overexposure are loss of appetite and nose bleed.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known

EMERGENCY AND FIRST AID PROCEDURES:

Skin Contact - Wash with soap and water for 15 minutes.
Eye Contact - Flush with warm water for 15 minutes. Seek medical attention.
Inhalation - Move victim to fresh air, if breathing has stopped give artificial respiration. Seek immediate medical attention.
Ingestion - Do not induce vomiting. Seek medical attention.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED: Eliminate all ignition sources, contain spill and shovel into an appropriate container.

WASTE DISPOSAL METHOD: Dispose of product in accordance with local, state and federal compliance regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: There should be no smoking in ther areas where this product is used. Keep away from all heat and ignition sources as well as oxidizing agents. Store material below 80°F and rotate stock continually.

SECTION IX - CONTROL MEASURES

RESPIRATORY PROTECTION: Use OSHA/NIOSH approved respirator with organic vapor cartridges in confined areas. 500 ppm: CCROV/SA/SCBA

VENTILATION	LOCAL EXHAUST:	If needed	SPECIAL :	N/A
	MECHANICAL :	If needed	OTHER :	N/A

GLOVES: Chemical resistant, impervious

EYE PROTECTION: Safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Use a chemical apron to protect clothing if needed.

WORK/HYGIENIC PRACTICES: Always wash hands after working with this material. Use good hygiene practices.

SECTION X - REGULATORY INFORMATION

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)
This product contains a chemical know to the State of California to cause bieth defects or other reproductive harm.

SARA Title III Information:

Section 313 - Toxic Chemicals

Pursuant to section 313 of SARA title III, this product contains one or more toxic chemicals that are present in a concentration in excess of 1 percent of the mixture (0.1 percent, if the listed toxic chemical is a carcinogen).

Toluene

Chalk
pg 3 of 6



MATERIAL SAFETY DATA SHEET

Schnee-Morehead[®], Inc.

SECTION XI - DISCLAIMER


This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

A MSDS such as this cannot be expected to cover all possible individual situations. The end user of this product has the responsibility to provide a safe workplace. All aspects of an individual operation should be examined to determine if, or where, precautions – in addition to those described herein – are required. Any health and safety information contained herein should be passed on to your customers and/or employees.

The opinions expressed herein are those of qualified experts within Schnee-Morehead[®], Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the use of this product are not within the control of Schnee-Morehead[®], Inc., final determination of suitability of this product is the sole responsibility of the user. It is the responsibility of the user to comply with all applicable Federal, State and Local laws and regulations.

=====

N/A = Not Applicable, N.A. = Not Available, N.D. = Not Determined, N/E = Not established, UNK = Unknown



MATERIAL SAFETY DATA SHEET

Schnee-Morehead®, Inc.

Paul h
pg. 4 of 6

SECTION VII - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION?: Yes SKIN?: Yes INGESTION?: Not Likely

HEALTH HAZARDS (ACUTE AND CHRONIC):

Like all urethane sealants, this product contains isocyanate resins which may cause irritation to the eyes or skin on contact. Tests have shown that no volatile isocyanates are present. Small amounts of residual toluene present may cause skin and respiratory tract irritation.

CARCINOGENICITY: NTP?: No IARC MONOGRAPHS?: No OSHA REGULATED?: Yes

SIGNS AND SYMPTOMS OF EXPOSURE: Upon exposure to the skin, the skin may turn red and burn. A person sensitive to organic solvents may have shortness of breath when using this product.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

This product may be irritating to a person with known allergies.

EMERGENCY AND FIRST AID PROCEDURES:

Eye Contact - Flush with warm water for 15 minutes and seek medical attention.

Skin Contact - Wash with warm water for 15 minutes. If irritation persists, contact a physician.

Inhalation - Move victim to fresh air. If breathing has stopped give artificial respiration. Seek immediate medical attention.

Ingestion - Do not induce vomiting. Seek medical attention.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Eliminate all ignition sources. Ventilate the area. Supply clean-up personnel with appropriate clothing (respirators, gloves, etc....), clean the material with mineral spirits or a mixture of toluene/alcohol if in an uncured state (wet and pliable). If the material is cured, use a solvent such as Dynasolve.

WASTE DISPOSAL METHOD:

Cured or neutralized waste product can be landfilled or incinerated. Consult and follow all local, state and federal compliance regulations before disposing of the product.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in a clean dry place. Moisture will cause the material to cure.

SECTION IX - CONTROL MEASURES

RESPIRATORY PROTECTION:

Not normally required for properly ventilated areas. Respiratory protection should be considered for exposures resulting from unusual applications and/or used in non-ventilated enclosed areas. If this occurs, wear NIOSH/MSHA approved self-contained breathing apparatus or cartridge type respirator.

VENTILATION	LOCAL EXHAUST:	If needed	SPECIAL :	N/A
	MECHANICAL :	If needed	OTHER :	N/A

GLOVES: Chemical resistant, impervious

EYE PROTECTION: Safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Use a chemical apron to protect clothing if needed.

WORK/HYGIENIC PRACTICES:

Always wash hands after working with this material; use good hygiene practices.


SECTION X - REGULATORY INFORMATION

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Information:

Section 313 - Toxic Chemicals: Pursuant to section 313 of SARA Title III, this product contains one or more toxic chemicals that are present in a concentration in excess of 1 percent of the mixture (0.1 percent, if the listed toxic chemical is a carcinogen). Toluene



MATERIAL SAFETY DATA SHEET

Schnee-Morehead®, Inc.

Caulk
Pg 5 of 6

SECTION I - IDENTIFICATION

PRODUCT NAME : Permathane SM7100 / 7108
PRODUCT CODE : SM7100 / 7108
DESCRIPTION : One Part Polyurethane Sealant
HAZARDOUS CLASSIFICATION: Non Regulated
PROPER SHIPPING NAME : Not Applicable
SHIPPING DESCRIPTION : Not Required

H.M.I.S RATINGS:

H	F	R	P
1	2	0	G

SECTION II - MANUFACTURER

MANUFACTURER'S NAME : Schnee-Morehead, Inc.
STREET ADDRESS : 111 North Nursery Road, Irving, Texas
INFORMATION PHONE : 972-438-9111 **EMERGENCY PHONE** : 800-424-9300
DATE PREPARED : March 6, 2007 **SUPERSEDES DATE** : December 20, 2005

SECTION III - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	ACGIH TLV	OTHER LIMITS	PERCENT (WGT)
Butyl Benzyl Phthalate	85-68-7	5 mg/m3	5 mg/m3		4-20%
Toluene	108-88-3	200 ppm (TWA)	50 ppm (TWA)	188 mg/m3 (TWA)	<3%

SECTION IV - PHYSICAL PROPERTIES

SPECIFIC GRAVITY (H₂O=1) : 1.61 **BOILING POINT** : N/A
NONVOLATILE (% WEIGHT) : >97 **MELT/FREEZE PT** : N/A
SOLUBILITY IN WATER : Insoluble **VAPOR DENSITY** : N/A
EVAPORATION RATE (BuAc=1) : N/A **VAPOR PRESSURE** : N/A
VOLATILE ORGANIC CONTENT : 0.40 lbs/gal or 48 g/l
APPEARANCE/ODOR : Color of pigment, pumpable material - slight aromatic odor

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : 136°F **METHOD USED** : ASTM D56 (TAG Closed Cup)
FLAMMABLE LIMITS IN AIR BY VOLUME **LOWER** : N/A **UPPER** : N/A

EXTINGUISHING MEDIA : Use carbon dioxide, dry chemical, foam or water spray.

SPECIAL FIREFIGHTING PROCEDURES : Firefighters should wear full emergency equipment with self-contained breathing apparatus. Irritating or toxic gasses may build up and possibly explode.

UNUSUAL FIRE AND EXPLOSION HAZARD : Overheated, closed containers adjacent to fire can cause the material inside to decompose resulting in pressure build up and possible explosion.

SECTION VI - REACTIVITY DATA

STABILITY : Stable

CONDITIONS TO AVOID : Material will start to cure in the presence of humid air or moisture.

INCOMPATIBILITY (MATERIALS TO AVOID) : Avoid contact with alcohols, amines, strong bases and surface active materials.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS : During a fire this material may form carbon dioxide, carbon monoxide, nitrogen oxides and traces of isocyanates.

HAZARDOUS POLYMERIZATION : Will not occur.

SM7108MSDS.doc

Page 1 of 3

Caulh
pg 6 of 6



MATERIAL SAFETY DATA SHEET

Schnee-Morehead[®], Inc.

SECTION XI - DISCLAIMER

This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

A MSDS such as this cannot be expected to cover all possible individual situations. The end user of this product has the responsibility to provide a safe workplace. All aspects of an individual operation should be examined to determine if, or where, precautions – in addition to those described herein – are required. Any health and safety information contained herein should be passed on to your customers and/or employees.

The opinions expressed herein are those of qualified experts within Schnee-Morehead[®], Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the use of this product are not within the control of Schnee-Morehead[®], Inc., final determination of suitability of this product is the sole responsibility of the user. It is the responsibility of the user to comply with all applicable Federal, State and Local laws and regulations.

=====

N/A = Not Applicable, N.A. = Not Available, N.D. = Not Determined, N/E = Not established, UNK = Unknown