
Coolant-Steel

FUCHS LUBRICANTS CO.



MANUFACTURER IDENTIFICATION Company Name : FUCHS LUBRICANTS CO. Address : 17050 LATHROP AVE. HARVEY IL 60426 Telephone : 708-333-8900 Emergency Contact . : Regulatory Compliance Department Emergency Telephone . : 708-333-8900 (8am - 5pm CST, M-F) 800-255-3924 (24 Hours) MSDS PRINT DATE : 03/16/2006 * EMERGENCY OVERVIEW This product is a water soluble liquid. Direct eye contact may cause irritation. Short term skin contact may cause slight irritation. Inhalation of high vapor or mist levels in poorly ventilated areas may cause mild upper respiratory tract irritation Ingestion is not an anticipated route of exposure. * HMIS Rating: Health- 1 Flammability- 0 Reactivity- 0 PPE- X SECTION 2 - COMPONENT DATA Components listed in this section may contribute to the potential hazards associated with exposure to the concentrate. The product may contain additional non-hazardous or trade-secret components. Monoethanolamine Cas#: 141-43-5 Percent: < 5 Exposure Limit: OSHA PEL/ACGIH TWA: 3 ppm OSHA/ACCIH STEL: 6 ppm Triethanolamine Cas#: 102-71-6 Percent: < 10 Exposure Limit: OSHA PEL/ACGIH TWA: 5mg/m3	SECTION 1 - P	RODUCT AND COMPANY IDENTIFICATION
Company Name . : FUCHS LUBRICANTS CO. Address . : 17050 LATHROP AVE. HARVEY IL 60426 Telephone . : 708-333-8900 Emergency Contact . : Regulatory Compliance Department Emergency Telephone . : 708-333-8900 (8am - 5pm CST, M-F) 800-255-3924 (24 Hours) MSDS PRINT DATE . : 03/16/2006 * EMERGENCY OVERVIEW This product is a water soluble liquid. Direct eye contact may cause irritation. Short term skin contact may cause slight irritation. Inhalation of high vapor or mist levels in poorly ventilated areas may cause mild upper respiratory tract irritatior Ingestion is not an anticipated route of exposure. * HMIS Rating: Health- 1 Flammability- 0 Reactivity- 0 PPE- X SECTION 2 - COMPONENT DATA Components listed in this section may contribute to the potential hazards associated with exposure to the concentrate. The product may contain additional non-hazardous or trade-secret components. Monoethanolamine Exposure Limit: OSHA PEL/ACGIH TWA: 3 ppm OSHA/ACGIH STEL: 6 ppm Triethanolamine Cas#: 141-43-5 Percent: < 5 Percent: < 7 Percent: <	PRODUCT IDENTIFICATION:	: ECOCOOL SYN 935-500GL BIN
Direct eye contact may cause irritation. Short term skin contact may cause slight irritation. Inhalation of high vapor or mist levels in poorly ventilated areas may cause mild upper respiratory tract irritation Ingestion is not an anticipated route of exposure. * HMIS Rating: Health- 1 Flammability- 0 Reactivity- 0 PPE- X SECTION 2 - COMPONENT DATA Components listed in this section may contribute to the potential hazards associated with exposure to the concentrate. The product may contain additional non-hazardous or trade-secret components. Monoethanolamine Cas#: 141-43-5 Percent: < 5 Exposure Limit: OSHA PEL/ACGIH TWA: 3 ppm OSHA/ACGIH STEL: 6 ppm Triethanolamine Cas#: 102-71-6 Percent: < 10 Exposure Limit: OSHA PEL/ACGIH TWA: 5mg/m3	MANUFACTURER IDENTIFICATION Company Name	: FUCHS LUBRICANTS CO. : 17050 LATHROP AVE. HARVEY IL 60426 : 708-333-8900 : Regulatory Compliance Department : 708-333-8900 (8am - 5pm CST, M-F) 800-255-3924 (24 Hours) : 03/16/2006
Components listed in this section may contribute to the potential hazards associated with exposure to the concentrate. The product may contain additional non-hazardous or trade-secret components. Monoethanolamine	Direct eye contact may ca cause slight irritation. poorly ventilated areas m Ingestion is not an antic	use irritation. Short term skin contact may Inhalation of high vapor or mist levels in ay cause mild upper respiratory tract irritation ipated route of exposure.
hazards associated with exposure to the concentrate. The product may contain additional non-hazardous or trade-secret components. Monoethanolamine	SEC	TION 2 - COMPONENT DATA
Exposure Limit: OSHA PEL/ACGIH TWA: 3 ppm OSHA/ACGIH STEL: 6 ppm Triethanolamine Exposure Limit: OSHA PEL/ACGIH TWA: 5mg/m3 Cas#: 102-71-6 Percent: < 10	hazards associated with exp	osure to the concentrate. The product may
Exposure Limit: OSHA PEL/ACGIH TWA: 5mg/m3	Exposure Limit: OSHA PEL/ACGIH TWA: 3	ppm
Carginogonia Componenta. This product contains no carginogens	Exposure Limit:	
- carcinogenic components: This produce contains no carcinogens.	- Carcinogenic Components:	This product contains no carcinogens.

POTENTIAL HEALTH EFFECTS and SYMPTOMS from SHORT TERM/ACUTE EXPOSURE: - EYE EXPOSURE -

This product is not expected to cause eye irritation under normal conditions of use. Symptoms of mild eye irritation and redness may result upon direct contact or when exposed to high mist levels in poorly ventilated areas.

Coolant-Steel
18/2009

PRODUCT NAME: ECOCOOL SYN 935-500GL BIN

- SKIN EXPOSURE Skin contact may result in slight, temporary irritation.
- INHALATION This product has low volatility and so is not expected to cause respiratory tract irritation during normal conditions of use. Exposure to high mist levels in poorly ventilated areas may irritate the upper respiratory tract with symptoms of itching eyes and nasal passages.
- INGESTION Ingestion may cause slight stomach irritation and discomfort.

POTENTIAL CHRONIC HEALTH EFFECTS: No further data known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: No further data known.

CARCINOGENICITY:

This product is not listed as a known or suspected carcinogen by IARC, OSHA, or the NTP.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. If symptoms persist, contact a physician.

SKIN CONTACT:

Remove product from the skin by washing with a mild soap and flushing with a steady stream of water. Contaminated clothing should be removed to prevent prolonged exposure. If symptoms of exposure persist, contact a physician.

INHALATION:

If signs or symptoms of overexposure occur, remove the employee to fresh air. If symptoms persist, seek medical attention.

INGESTION:

If small amounts are ingested, first aid measures are not likely to be necessary. If larger amounts are ingested or if symptoms of ingestion occur, dilute stomach contents with two glasses of water or milk. (NOTE: Do NOT give anything by mouth to an unconscious person.) Do not induce vomiting without medical supervision. If vomiting occurs spontaneously keep airway clear. If symptoms of ingestion persist, seek medical attention.

Pg. 3 of 7

PRODUCT NAME: ECOCOOL SYN 935-500GL BIN

NOTE TO PHYSICIAN:

No further data known.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES:

EXTINGUISHING MEDIA:

This product is not combustible but water fog, dry chemical, foam, and CO2 fire extinguishers may be used in areas where it is stored.

UNUSUAL FIRE & EXPLOSION HAZARDS:

No further data known.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

The noncombustible nature of the product creates no need for special fire fighting procedures and equipment.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP MEASURES:

Important: As with any spill or leak, before responding ensure that you are familiar with the potential hazards and recommendations of the MSDS. Appropriate personal protective equipment must be worn. See Section 8 of this MSDS for PPE recommendations.

If possible, safely contain the spill with dikes or other spill response equipment appropriate for releases of water-based materials. Prevent spreading of product and/or release into the environment. Large volumes of material should be collected in an appropriate waste container for proper disposal. Small volumes or residues may be soaked up with absorbent material. Disposal of any spill response materials should meet appropriate waste regulations.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

As with any industrial chemical, handle the product in a manner that minimizes exposure to practicable levels. Prior to handling, consult Section 8 of this MSDS to evaluate personal protective equipment needs. Open containers slowly to relieve any pressure. Follow all other standard industrial hygiene practices.

Empty containers may contain product residue. All safety precautions taken when handling this product should also be taken when handling empty

Coolant-Steel
184 of 7

PRODUCT NAME: ECOCOOL SYN 935-500GL BIN

drums and containers. Keep containers closed when not in use.

STORAGE:

Protect product quality by storing indoors and away from extreme temperatures. Close all containers when not in use.

SPECIAL COMMENTS:

Do not mix with nitrites. This product contains an amine that may react, under certain conditions, with nitrites to form nitrosamines.

No further data known.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT:

Selection of personal protective equipment should be based upon the anticipated exposure and made in accordance with OSHA's Personal Protective Equipment Standard found in 29 CFR 1910 Subpart I. The following information may be used to assist in PPE selection.

- EYE PROTECTION -

Wear eye protection appropriate to prevent eye exposure. Where splashing is not likely, chemical safety glasses with side shields are recommended. Where splashing may occur, chemical goggles or full face shield is recommended.

- SKIN PROTECTION -

Gloves are not normally needed during normal conditions of use. If health effects are experienced, oil or chemical resistent gloves such as butyl or nitrile are recommended.

Where splashing or soaking is likely, wear oil or chemical resistent clothing to prevent exposure.

- RESPIRATORY PROTECTION -

A respirator may be worn to reduce exposure to vapors, dust, or mist. Select a NIOSH/MSHA approved respirator appropriate for the type and physical character of the airborne material. A self-contained breathing apparatus is recommended in all situations where airborne contaminant concentration has not been confirmed to be below safe levels. Respirator use should comply with the OSHA Respirator Protection Standard found in 29 CFR 1910.134.

ENGINEERING CONTROLS:

Normal general ventilation is expected to be adequate. It is recommended that ventilation be designed in all instances to maintain airborne concentrations at lowest practicable levels. Ventilation should at a minimum, prevent airborne concentrations from exceeding any exposure

pg 5 of 7 1/8/2009

PRODUCT NAME: ECOCOOL SYN 935-500GL BIN

limits listed in Section 2 of this MSDS.

The user may wish to refer to 29 CFR 1910.1000(d)(2) and the ACGIH "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indicies" (Appendix C) for the determination of exposure limits of mixtures. An industrial hygienist or similar professional may be consulted to confirm that the calculated exposure limits apply.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance Yellow

Physical State : Liquid Water Solubility : Soluble Specific Gravity : 1.050

SECTION 10 - STABILITY AND REACTIVITY

INCOMPATIBILITIES:

This product is incompatible with strong oxidizing agents.

DECOMPOSITION PRODUCTS MAY INCLUDE:

The product, as sold, is not expected to thermally decompose. Product residue however, may burn. Thermal decomposition products are highly dependent on combustion conditions. A complex mixture of airborne solid liquid, particulates and gasses may evolve when the residues burn. Byproducts of residue combustion may include:

oxides of carbon,

traces of formaldehyde,

ammonia and oxides of nitrogen,

incompletely burned hydrocarbons as fumes and smoke.

CONDITIONS TO AVOID:

Avoid contact with incompatible materials and exposure to extreme temperatures.

POLYMERIZATION:

This product is not expected to polymerize.

STABILITY:

This product is stable.

SECTION 11 - TOXICOLOGICAL INFORMATION

EYE EFFECTS:

No further toxicological data known.

Coolant-Steel
P3 6 of 7
1/8/2009

PRODUCT NAME: ECOCOOL SYN 935-500GL BIN	
SKIN EFFECTS: Contact with a component of this produ reaction in a small percentage of the	ct may cause an allergic skin population.
No further toxicological data known.	
ORAL EFFECTS: No further toxicological data known.	
INHALATION EFFECTS: No further toxicological data known.	
OTHER: No further data known.	
SECTION 12 - ECOLOGI	CAL INFORMATION
ENVIRONMENTAL FATE: The degree of biodegradability and perbeen determined.	sistence of this product has not
SECTION 13 - DISPOSA	L CONSIDERATIONS
WASTE DISPOSAL: Ensure that collection, transport, tre product, containers and rinsate compli regulations. Note that use, mixture, product may cause the material to be contained in the responsibility of the product time of disposal, whether the product	es with all applicable laws and processing, or contamination of the lassified as a hazardous waste. t user or owner to determine at the
SECTION 14 - TRANSP	ORT INFORMATION
DOT HAZARDOUS MATERIAL INFORMATION: * Not otherwise DOT regulated.	
SECTION 15 - REGULAT	ORY INFORMATION
FEDERAL REGULATIONS: SARA 313: This product contains NONE of the su requirements of Section 313 of Title	bstances subject to the reporting III of the Superfund Amendments

Coolant. Steel Pg 70f7 1/8/2009

PRODUCT	NAME:	ECOCOOL	SYN	935-500GL	BIN

and Reauthorization Act of 1986 and 40 CFR Part 372.

CERCLA Reportable Quantity:

Any components listed below have been assigned a reportable quantity (RQ) by the Federal EPA. Releases of the product into the environment that exceed the RQ for a particular component must be reported to the National Response Center at 1-800-424-8802.

Component										RQ																
*		*		*		*		*		*	3	*		*		*		*		*		*		*	*	_

Toxic Substances Control Act:

The components of this product are listed on the TSCA Inventory.

Ozone Depleting Substances:

This product contains no ozone depleting substances as defined by the Clean Air Act.

Hazardous Air Pollutants:

Any components listed below are defined by the Federal EPA as hazardous air pollutants.

Component																									
*	-	*	-	*	_	*	_	*	-	*	-	*	_	*	-	*	_	*	_	*	-	*	_	*	 4

STATE REGULATIONS:

No further data known.

SECTION 16 - OTHER INFORMATION

NOTICE: This MSDS provides a good faith representation of information believed to be accurate as of the last revision date. This document does not create any express or implied product warranties. Since conditions of use are beyond the control of Fuchs Lubricants Co., all risks associated with product use are assumed by the user.