



**MATHESON
TRI-GAS**

ask. . .The Gas Professionals™

Page 1 of 6

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MATHESON TRI-GAS, INC.
150 Allen Road Suite 302
Basking Ridge, New Jersey 07920
Information: 1-800-416-2505

Emergency Contact:
CHEMTREC 1-800-424-9300
Calls Originating Outside the US:
703-527-3887 (Collect Calls Accepted)

SUBSTANCE: NITROUS OXIDE

TRADE NAMES/SYNONYMS:

MTG MSDS 70; DINITROGEN MONOXIDE; FACTITIOUS AIR; LAUGHING GAS; HYPONITROUS ACID ANHYDRIDE; NITROGEN (I) OXIDE; NITROGEN OXIDE; UN 1070; NITROGEN OXIDE (N₂O); DINITROGEN OXIDE; NITROUS OXIDE, COMPRESSED; N₂O; MAT16790; RTECS QX1350000

CHEMICAL FAMILY: inorganic, gas

CREATION DATE: Jan 24 1989


REVISION DATE: Sep 13 2007

2. COMPOSITION, INFORMATION ON INGREDIENTS

COMPONENT: NITROUS OXIDE
CAS NUMBER: 10024-97-2
PERCENTAGE: 100.0

3. HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4): HEALTH=1 FIRE=0 REACTIVITY=0



EMERGENCY OVERVIEW:

COLOR: colorless

PHYSICAL FORM: gas

ODOR: sweet odor

MAJOR HEALTH HAZARDS: potentially fatal if inhaled, central nervous system depression, difficulty breathing

PHYSICAL HAZARDS: Containers may rupture or explode if exposed to heat.

POTENTIAL HEALTH EFFECTS:

INHALATION:

SHORT TERM EXPOSURE: nausea, vomiting, symptoms of drunkenness, hyperactivity or drowsiness, hearing loss, suffocation, death

LONG TERM EXPOSURE: tingling sensation, impotence, reproductive effects

SKIN CONTACT:

SHORT TERM EXPOSURE: blisters, frostbite

LONG TERM EXPOSURE: no information is available

EYE CONTACT:

SHORT TERM EXPOSURE: frostbite, blurred vision

LONG TERM EXPOSURE: no information is available

INGESTION:

SHORT TERM EXPOSURE: frostbite

LONG TERM EXPOSURE: no information is available

4. FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

SKIN CONTACT: If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

EYE CONTACT: Flush eyes with plenty of water.

INGESTION: If a large amount is swallowed, get medical attention.

NOTE TO PHYSICIAN: For inhalation, consider oxygen.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Negligible fire hazard. Containers may rupture or explode if exposed to heat. Gas/air mixtures are explosive.

EXTINGUISHING MEDIA: carbon dioxide, regular dry chemical

Large fires: Use regular foam or flood with fine water spray.

FIRE FIGHTING: Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Use extinguishing agents appropriate for surrounding fire. Cool containers with



water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Do not get water directly on material. Reduce vapors with water spray. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Consider downwind evacuation if material is leaking.

6. ACCIDENTAL RELEASE MEASURES

OCCUPATIONAL RELEASE:

Stop leak if possible without personal risk. Avoid contact with combustible materials. Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering.

7. HANDLING AND STORAGE

STORAGE: Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.105. Keep separated from incompatible substances.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE LIMITS:

NITROUS OXIDE:

50 ppm ACGIH TWA

25 ppm (46 mg/m³) NIOSH recommended TWA (halogenated anesthetic gas)

VENTILATION: Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

EYE PROTECTION: For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

CLOTHING: For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

GLOVES: Wear insulated gloves.

RESPIRATOR: Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Respiratory protection is ranked in order from minimum to maximum. Consider warning properties before use.

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

For Unknown Concentrations or Immediately Dangerous to Life or Health -



Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: gas

COLOR: colorless

ODOR: sweet odor

TASTE: sweet taste

MOLECULAR WEIGHT: 44.01

MOLECULAR FORMULA: N₂-O

BOILING POINT: -128 F (-89 C)

FREEZING POINT: -132 F (-91 C)

VAPOR PRESSURE: 760 mmHg @ -88 C

VAPOR DENSITY (air=1): 1.530

SPECIFIC GRAVITY: Not applicable

DENSITY: 1.8122 g/L @ 25 C

WATER SOLUBILITY: 59% @ 25 C

PH: Not applicable

VOLATILITY: Not applicable

ODOR THRESHOLD: Not available

EVAPORATION RATE: Not applicable

VISCOSITY: 0.0145 cP @ 25 C

COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable

SOLVENT SOLUBILITY:

Soluble: sulfuric acid, alcohol, alkali solutions, ether, oils

10. STABILITY AND REACTIVITY

REACTIVITY: Stable at normal temperatures and pressure.


CONDITIONS TO AVOID: Avoid contact with combustible materials. Protect from physical damage and heat. Containers may rupture or explode if exposed to heat.

INCOMPATIBILITIES: combustible materials, metals, bases, reducing agents, peroxides, metal salts, metal oxides

HAZARDOUS DECOMPOSITION:

Thermal decomposition products: oxides of nitrogen

POLYMERIZATION: Will not polymerize.



**MATHESON
TRI-GAS**

ask. . .The Gas Professionals™

Page 5 of 6

11. TOXICOLOGICAL INFORMATION

NITROUS OXIDE:

CARCINOGEN STATUS: IARC: Human Inadequate Evidence, Animal Inadequate Evidence, Group 3 (Anesthetics, volatile); ACGIH: A4 -Not Classifiable as a Human Carcinogen

TARGET ORGANS: central nervous system

MUTAGENIC DATA: Available.

REPRODUCTIVE EFFECTS DATA: Available.

12. ECOLOGICAL INFORMATION

Not available

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable regulations.

14. TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:

PROPER SHIPPING NAME: Nitrous oxide

ID NUMBER: UN1070

HAZARD CLASS OR DIVISION: 2.2

LABELING REQUIREMENTS: 2.2; 5.1



CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

SHIPPING NAME: Nitrous oxide

UN NUMBER: UN1070

CLASS: 2.2; 5.1

15. REGULATORY INFORMATION

U.S. REGULATIONS:

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4): Not regulated.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30): Not regulated.

SARA TITLE III SECTION 304 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.40): Not regulated.

SARA TITLE III SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40 CFR 370.21):

ACUTE: Yes

CHRONIC: No

FIRE: No

REACTIVE: No

SUDDEN RELEASE: Yes

SARA TITLE III SECTION 313 (40 CFR 372.65): Not regulated.

OSHA PROCESS SAFETY (29CFR1910.119): Not regulated.

STATE REGULATIONS:

California Proposition 65: Not regulated.

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION: A, C.

NATIONAL INVENTORY STATUS:

U.S. INVENTORY (TSCA): Listed on inventory.

TSCA 12(b) EXPORT NOTIFICATION: Not listed.

CANADA INVENTORY (DSL/NDL): Not determined.

16. OTHER INFORMATION

MSDS SUMMARY OF CHANGES

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

©Copyright 1984-2007 MDL Information Systems, Inc. All rights reserved.

MATHESON TRI-GAS, INC. MAKES NO EXPRESS OR IMPLIED WARRANTIES, GUARANTEES OR REPRESENTATIONS REGARDING THE PRODUCT OR THE INFORMATION HEREIN, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR USE. MATHESON TRI-GAS, INC. SHALL NOT BE LIABLE FOR ANY PERSONAL INJURY, PROPERTY OR OTHER DAMAGES OF ANY NATURE, WHETHER COMPENSATORY, CONSEQUENTIAL, EXEMPLARY, OR OTHERWISE, RESULTING FROM ANY PUBLICATION, USE OR RELIANCE UPON THE INFORMATION HEREIN.